

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application No. : 10/713325 Confirmation No. 1245
Applicant : Stephen Kyle
Filed : November 14, 2003
TC/A.U. : 2877
Examiner : N/A

Title : METHOD AND DEVICE FOR CALIBRATING A
MEASURING SYSTEM
Docket No. : FRR-15081
Customer No. : 007609

SUBSTITUTE SPECIFICATION

(Filed under §1.125(b))

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir/Madam:

Enclosed herewith is a substitute specification for filing in the above-identified application. The undersigned hereby certifies that the substitute specification includes no new matter. A marked-up copy of the substitute specification showing the matter being added to and the matter being deleted from the specification of record is also included.

If there are any additional fees resulting from this communication, please charge same to our Deposit Account No. 18-0160, Our Order No. FRR-15081.

Respectfully submitted,

RANKIN, HILL, PORTER & CLARK LLP

By


David E. Spaw, Reg. No. 34732


700 Huntington Building
925 Euclid Avenue
Cleveland, Ohio 44115-1405
(216) 566-9700

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date indicated below.


Signature of Person Mailing Paper

3/4/04
Date

David E. Spaw
Printed Name of Person Mailing Paper



METHOD AND DEVICE FOR CALIBRATING A MEASURING SYSTEM

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

[0001] The present invention is situated in the field of measuring technology (metrology) and concerns a method and a device for calibrating a measuring system that is applicable for determining spatial position and orientation of objects and that comprises a measuring device with a laser tracker and an opto-electronic sensor, a system computer, and an auxiliary measuring tool.

DESCRIPTION OF RELATED ART

[0002] The term laser tracker or tracker in the present context is a device comprising means for generating an optical measuring beam, advantageously a laser beam, an optical system for aligning the measuring beam to a target point (e.g. cube edge prism) reflecting the measuring beam back to the measuring device in parallel, means for analysing the reflected measuring beam for determining the absolute or relative path length of the beam, and means for detecting the absolute or relative direction of the measuring beam. From the recorded data regarding beam path length and beam direction between laser tracker and reflector (target point), spatial co-ordinates of the reflector relative to the laser tracker can be calculated. The optical system of the tracker advantageously is equipped such that the measuring beam is able to automatically track a moving target point. Laser trackers of the Leica Geosystems company are available on the market. Other devices such

as, for example, motorised theodolites comprising distance measurement means, also fall under the above definition.

[0003] The term opto-electronic sensor in the present context is a device equipped for creating an electronically evaluable, two-dimensional image of a spatial arrangement of light spots. The opto-electronic sensor comprises a two-dimensional, light-sensitive array and a combination of lenses with an optical axis. It is, for example, a CCD or CID-camera or it is based on a CMOS-array. For evaluating the two-dimensional image, means are provided for identifying the imaged light spots, for determining the centers of gravity of the imaged light spots and for determining the image co-ordinates of these centers of gravity. From these coordinates, spatial angles between the optical axis of the sensor and the direction from the sensor to the light spots can be calculated.

[0004] The laser tracker and the opto-electronic sensor in the measuring device of the measuring system presented here are installed one on top of the other such that their positions relative to one another are fixed. For example, the laser tracker and sensor are rotatable together around an essentially vertical axis, and the sensor can be pivoted upwards and downwards independent of the laser tracker.

[0005] Measuring devices with a laser tracker and an opto-electronic sensor in accordance with the above definitions and with a system computer for carrying out the mentioned calculations and their utilization for determining spatial position and orientation of objects carrying light spots and reflectors belong to the state of the art. Measuring devices of this kind are available on the market (e.g., theodolite type T3000V/D of the Leica company). When using a measuring device of the named type for determining position and orientation of an object, at least three light points to

be detected by the opto-electronic sensor and at least one reflector reflecting the measuring beam of the laser tracker are arranged on the object in known positions relative to the object. The light spots to be registered by the opto-electronic sensor may be active light sources (e.g. light-emitting diodes) or reflectors to be illuminated, wherein the light spots are equipped or arranged such that they can be identified in an unequivocal manner.

[0006] In many applications not the object, the position and orientation of which is sought, is measured itself but an auxiliary measuring tool, which belongs to the measuring system and which, for the measurement, is brought into a position relative to the target object, which position is mechanically defined or is determined during the measurement. From the measured position and orientation of the auxiliary measuring tool the sought position and, if so required, orientation of the target object can be calculated. Auxiliary measuring tools are, for example, so-called touch tools that are positioned on a target object with their contact point in contact with the target object. Light spots and reflector of the touch tool have exactly known positions relative to the contact point. Touch tools of the type are available on the market (e.g., Optrek 3-D Co-ordinate Measuring Stylus of Northern Digital Corp. Canada). However, the auxiliary measuring tool may also be a hand-held scanner for contact-free surface measurements. The scanner is equipped for distance measurement with the aid of a measuring beam and it comprises light spots and reflectors in known positions relative to direction and position of the measuring beam. A scanner of this kind is described, for example, is discussed in the publication EP-0553266 (Schulz).

[0007] It is obvious that, in a measuring system as described above, the laser tracker and the reflector (or the reflectors) of the auxiliary measuring tool, on the one hand, and the opto-electronic sensor and the light spots of the auxiliary measuring tool, on the other hand, represent separate measuring systems being coupled with one another through the relative arrangement of laser tracker and opto-electronic sensor in the measuring device and through the relative arrangement of light spots and reflector or reflectors on the auxiliary measuring tool. For correlating the two measuring systems, calibration is necessary. Calibration concerns the laser tracker and the opto-electronic sensor of the measuring device and the auxiliary measuring tool.

SUMMARY OF THE INVENTION

[0008] The present invention is directed toward a method and a device that serves to calibrate or correlate the two measuring systems mentioned above. Use of the method and device according to the invention allows a very simple calibration of a measuring system comprising a system computer, a measuring device with a laser tracker and an opto-electronic sensor, and an auxiliary measuring tool with at least three light spots and at least one reflector. The calibration consists of measuring steps and calculating steps producing calibration data for coupling measured data determined by the laser tracker and by the opto-electronic sensor with respect to the auxiliary measuring tool such that the measured data can at all times be related to a common coordinate system, e.g. of the laser tracker. The measuring steps of the calibration method in accordance with the invention, for which the device according

to the invention is used, are to be so simple that they can be carried out with great accuracy by a user of the measuring system, e.g. on commissioning a new auxiliary measuring tool.

[0009] The calibration procedure according to the invention comprises essentially the following steps:

- If the auxiliary measuring tool comprises less than three reflectors, the number of reflectors is complemented to at least three with auxiliary reflectors. If so required, the relative positions of reflector(s) and auxiliary reflectors are determined.
- The auxiliary measuring tool, if applicable together with the auxiliary reflectors, is rotated around at least two rotation axes that, relative to the auxiliary measuring tool, are different from one another. In at least two rotation positions relative to each one of the rotation axes, the at least three light spots of the auxiliary measuring tool are registered by the opto-electronic sensor and the at least three reflectors are registered by the laser tracker. For all these measurements the position of the measuring device remains unchanged.
- For each one of the rotation positions of the auxiliary measuring tool, the position and orientation of the reflector arrangement relative to the laser tracker and of light spot arrangement relative to the opto-electronic sensor are calculated from the measured data by the laser tracker and by the opto-electronic sensor registered in the above-described measuring step.
- From the positions and orientations of the reflector arrangement and of the light spot arrangement, the direction and position of the at least two

rotation axes relative to the reflector arrangement and relative to the light spot arrangement are calculated. For this purpose, data with respect to the known, relative positions of the light spots and, if applicable, of the reflectors are necessary.

- Corresponding rotation axes calculated relative to the reflector arrangement and relative to the light spot arrangement are then equated with one another and, from these equations, calibration data are calculated, which for the calibrated pair of measuring device and auxiliary measuring tool allow data transformation from the tracker/reflector system to the sensor/light spot system and vice versa. Such calibration data is, for example, necessary for calculating any position and orientation of the auxiliary measuring tool relative to any coordinate system from data registered by the tracker and the sensor.
- The calibration device in accordance with the invention serves to bring the auxiliary measuring tool into the various rotation positions around the different rotation axes and, if so required, for combining it with auxiliary reflectors. For this purpose, the device comprises installation means for accurately mounting the auxiliary measuring tool in different orientations, wherein the auxiliary measuring tool may be equipped with installation means co-operating with the installation means of the calibration device. If auxiliary reflectors are necessary for the calibration (if the auxiliary measuring tool comprises less than three reflectors), the calibration device further comprises a reflector element to be rigidly coupled with the

auxiliary measuring tool and to be mounted on the calibration device in the different orientations, together with the auxiliary measuring tool.

[0010] The calibration device, for example, comprises a revolving table on which the auxiliary measuring tool, if so required together with the reflector element, is mounted in at least two different orientations, and which is rotated for bringing the auxiliary measuring tool into different rotation positions. The calibration device may also be designed non-rotating and allowing installation positions and orientations for auxiliary measuring tool and possibly reflector element, which equal different rotation positions around at least two rotation axes being different relative to the auxiliary measuring tool.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] These and further features of the invention will be apparent with reference to the following description and drawings, wherein all Figures illustrate the same advantageous embodiment of the reflector and target point arrangement on the auxiliary measuring tool, which, however, does not represent a condition for the invention.

[0012] Figure 1 shows an exemplary, as such known measuring system, for which the calibration method and device according to the invention are suitable;

[0013] Figure 2 shows the auxiliary measuring tool of the measuring system in accordance with Fig. 1, the instrument being provided with auxiliary reflectors for calibration;

[0014] Figure 3 shows an exemplary embodiment of the calibration device according to the invention, which device is suitable for calibration of the measuring system according to Fig. 1;

[0015] Figures 4 to 6 show successive steps of the calibration method according to the invention; and,

[0016] Figure 7 shows a reflector being also equipped as a light spot and being applicable for the auxiliary measuring tool.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0017] Figure 1 shows in a very schematic manner an exemplary, as such known measuring system, for which the calibration method and device according to the invention are suitable. The measuring system comprises a measuring device 1 in which a laser tracker 2 and an opto-electronic sensor 3 are installed one on top of the other or integrated into one another such that their relative positions are fixed. The measuring system further comprises a not illustrated system computer.

[0018] The measuring system further comprises an auxiliary measuring tool 4, which in the case illustrated comprises one reflector 5 and four identifiable light spots 6. In Fig. 1 as well as in all following drawing figures, only those parts of the auxiliary measuring tool relevant for the calibration are shown, namely the arrangement of reflector 5 and light spots 6. The auxiliary measuring tool may comprise any shape suitable for its measuring function. The reflector 5 is equipped for parallel reflection of the measuring beam 7 of the laser tracker 2. For example, the reflector is a cube corner prism. The light spots 6 to be registered by the opto-electronic sensor are, for

example, LEDs or reflecting spots being correspondingly illuminated for measurements. The light spots 6 are unequivocally identifiable either through their relative arrangement or through corresponding identification means.

[0019] A three-dimensional arrangement (not in one plane) of the four light spots 6 and an arrangement of the reflector in a central zone of the light spot arrangement are known to be advantageous for measurements. This is also advantageous for the calibration in accordance with the invention, but is not a condition. An auxiliary measuring tool with a single reflector is advantageous, particularly for applications in which the auxiliary measuring tool 4 is automatically tracked by the laser tracker 2.

[0020] As already mentioned further above, the auxiliary measuring tool 4 is, for example, a touch tool, the contact point of which is positioned on points to be measured. The auxiliary measuring tool may also be a scanner being equipped for contact-free distance measurement and being guided over an object to be measured by hand.

[0021] Figure 2 illustrates the auxiliary measuring tool 4 of Fig. 1 being combined with four auxiliary reflectors-5'. These auxiliary reflectors 5' are arranged on a reflector element 10 (e.g., a reflector plate). The reflector element 10 for an auxiliary measuring tool with less than three reflectors is a necessary component of the calibration device. The reflector element 10 is designed to be rigidly coupled with the auxiliary measuring tool. The arrangement of the in total e.g. five reflectors advantageously is three-dimensional.

[0022] Figure 3 depicts an exemplary embodiment of the calibration device 9 according to the invention, wherein the auxiliary measuring tool of Figs. 1 and 2 is installed on the calibration device. The device comprises the reflector element 10 of

Fig. 2, which is designed to be rigidly coupled with the auxiliary measuring tool, and a revolving table 11 with a stationary rotation axis C and carrying wedge shaped orientation element 12. The orientation element 12 comprises installation means (not shown) for mounting the auxiliary measuring tool 4 or the auxiliary measuring tool 4 rigidly coupled to the reflector element 10 respectively in at least two different orientations. In place of the revolving table 11 an element can be provided that comprises at least two groups of at least two installation positions for the auxiliary measuring tool 4 possibly together with the reflector element 10, wherein the orientations of each group are such that they are convertible into one another by rotation around a stationary, virtual rotation axis.

[0023] It appears that theoretically the angle between the two different rotation axes to be established by mounting the auxiliary measuring tool to the calibration device is optimally 90° . When utilising reflectors with an opening angle of $\pm 20^\circ$, the named angle can only be around 25 to 30° . However, the smaller angle gives satisfactory accuracy also.

[0024] Figures 4 and 5 illustrate the measuring arrangement for the method in accordance with the invention. The measuring device 1 advantageously is positioned relative to the calibration device 9 such that the optical axis of the opto-electronic sensor 3 is approximately aligned to the rotation axis C of the revolving table, and such that the light spot arrangement of the auxiliary measuring tool 4 can be registered fully and as large as possible on the image surface of the opto-electronic sensor in all foreseen rotation positions.

[0025] Fig. 4 illustrates the measuring arrangement for a first rotation axis relative to the measuring instrument 4. Fig. 5 illustrates the same measuring arrangement

for a second rotation axis relative to the measuring instrument 4. The two measuring arrangements differ by the fact that the auxiliary measuring tool 4 together with the reflector element 10 is turned by 180° on the orientation element 12 such that the stationary rotation axis C traverses the measuring instrument 4 advantageously in a central zone in both cases, but in two different directions and advantageously in two different places.

[0026] If the relative positions of the light spots and, if so required, of the reflectors and auxiliary reflectors are not known in advance, these have to be determined for the calculation of the calibration data. The relative positions of the light spots are, for example, determined by multiple registration with the opto-electronic sensor or a similar device and by bundle adjustment. For this purpose, a coordinate system 30 proprietary to the light spot arrangement is selected. The coordinate system 30 advantageously has an origin in the central zone of the light spot arrangement and a z-axis, which, in the calibration arrangement, is directed towards the measuring instrument 1. The relative positions of the reflectors, for example, are determined with the tracker or with another device with similar functions. For this purpose, a coordinate system 31 proprietary to the reflector arrangement is selected, the origin of which lies in one of the auxiliary reflectors and the z-axis of which stands vertically on the reflector plate.

[0027] From the measured data registered with the arrangements according to Figs. 4 and 5 by the laser tracker and the opto-electronic sensor and regarding, for each orientation of the auxiliary measuring tool (each different rotation axis), at least two rotation positions of the light spot arrangement and of the reflector arrangement, data regarding the relative positions and orientations of the light spot arrangement

relative to the opto-electronic sensor and data of the relative positions and orientation of the reflector arrangement relative to the laser tracker are computed, for which purpose various, as such known mathematical models are available.

[0028] Positions and orientations of the light spot arrangement relative to the opto-electronic sensor are calculated, for example, with an iterative reverse intersection method, wherein as starting values a position of the origin of the coordinate system 30 on the optical axis of the opto-electronic sensor and a rotation matrix based on parallel projection and taking the optical axis as rotation axis are utilised.

[0029] Positions and orientations of the reflector arrangement relative to the laser tracker may be calculated, for example, by aligning the local axes (local axis alignment), for which purpose the relative positions of the reflectors in the reflector arrangement have to be known. Alternatively, a mathematical circle model (e.g., Axyz-module of Leica) can be used.

[0030] In a further calculation step, for each rotation axis the direction and position in the coordinate systems 30 and 31 are calculated from positions and orientations associated with the specific rotation axis and determined for the reflector arrangement and the light spot arrangement in the previous steps. In Fig. 6, the reflector arrangement and the light spot arrangement with the coordinate systems 30 and 31 are separately illustrated and the two rotation axes in the two systems are designated with 1A and 1B on the one hand and 2A and 2B on the other hand.

[0031] In a third calculation step, in principle, axes 1A and 1B and axes 2A and 2B are equated with one another, from which equations results the sought calibration data. The calibration data is used for coordinate transformation from the coordinate

system 30 into the coordinate system 31 or vice versa or, more generally speaking, for transforming measuring data originating from the laser tracker in relation to the reflector (or reflectors) of the auxiliary measuring tool to calculations, which refer to measuring data originating from the opto-electronic sensor in relation to the light spots of the auxiliary measuring tool.

[0032] The generated calibration data are stored in the system computer for subsequent measuring processes. If a measuring system comprises a plurality of different auxiliary measuring tools, calibration is carried out for every one of the tools and the corresponding calibration data is stored together with a tool identification. Also stored in the system computer and capable of being activated for a calibration process are algorithms and programs required for the calibration and advantageously also directions for an operator who is to carry out the measuring steps of the calibration process.

[0033] Figure 7, in a once again very schematic manner, illustrates a cube corner prism applicable as a reflector 5 and at the same time as a light spot. Instead of the effective cube corner, the modified cube corner prism comprises a surface 41 that is parallel to the entrance/exit surface 40 and smaller than the diameter of the measuring beam of the laser tracker. Behind the surface 41, a light source 42, e.g., a light-emitting diode is arranged. The lighted diode makes the surface 41 into a light spot, which is detectable by the opto-electronic sensor. If, in the auxiliary measuring tool according to Fig. 1, instead of the reflector 5 a reflector/light spot combination according to Fig. 7 is used, this point will belong at the same time to the coordinate system of the light spot arrangement and to the coordinate system of the reflector arrangement, rendering calibration more simple. However, registration of

the corresponding light spot by the opto-electronic sensor is to be corrected depending on a deviation of the direction between the opto-electronic sensor and the surface 40, on the height of the prism between the surfaces 40 and 41, and on the refractive index of the prism material.